



DESIGNED TO GIVE AN AUTHENTIC SHINGLE EFFECT



- Educational buildings
- Commercial buildings
- 🗸 Flat to pitch
- ✓ Community centres
- Vertical cladding

- Holiday homes
- 🗸 Park homes
- 🗸 Camping pods
- 🗸 Stables
- Conservatories
- 🧹 Lean to's

RAISING THE STANDARDS IN LIGHTWEIGHT ROOFING





TECHNICAL DATA

Overall width: 1326mm

Batten gauge (0.40mm): 250mm

Roof cover per tile panel: 0.308m²

Tile panels per m²: 3.2 No per m²

Weight as laid per m²: Under 7kg

traditional roof tiles and slates

Fire resistance: AA classification equal to

Cover width: 1231mm

Steel base: 0.40mm

Min. pitch: 15°

Max. pitch: 90°

Side lap: 95mm

Step: 20mm

DESIGNED TO GIVE AN AUTHENTIC SHINGLE EFFECT

ADVANTAGES

- British made
- Designed to give a traditional shingle appearance
- Lightweight
- Low pitch
- Good vandal resistance
- Quick installation
- Cost effective
- Virtually maintenance free
- Extensive range of accessories and flashings available
- Fully dry-fixed
- Guaranteed for 40 years against weather penetration
- Full technical support available
- Hidden fixing

COLOURS AVAILABLE







Titanium Grey





Rustic Terracotta







Tartan Green

Acrylic Top Coat Stone Granules Acrylic Base Coat **Epoxy Primer** 0.40mm Galvanised Steel / Alu Zinc Base **Epoxy Primer Polyester Coating**







Smoked Oak



Kingfisher House, Unit 17, Overthorpe Road, Banbury OX16 4SX T +44 (0) 1295 250998 F +44 (0) 1295 271068 E sales@britmet.co.uk

APPROVALS:

Manufactured using ISO 9001 approved materials

www.britmet.co.uk

ISO 14001

