

**Data Sheet: Expanding Foam Tape – 8000 Range**

**Product Description**

Foam sealing tape, impregnated with an acrylic-based polymer. It is used to seal exterior seams and joints against driving rain in window installation, as well as metal, wood and container construction.

**Technical Data**

Properties		Value
Material:		Open-cell polyurethane soft foam with polymer impregnant
Colour:		Dark grey
Flammability class:	DIN 4102	B1 (flame retardant), P-NDS04-218
Water vapour permeability, sd-value:		< 0,5 m
Temperature resistance:		-30 °C to + 90 °C
Air permeability:	DIN EN 1026	$a \leq 0,1 \text{ m}^3 / [\text{h} \cdot \text{m} \cdot (\text{daPa})^n]$
Weather resistance:	DIN 18542	Complies with requirements
Grouping according to:	DIN 18542	BG1
Resistance to driving rain:	DIN EN 1027	Complies with requirements up to 600 Pa
Properties		Value
Compatibility with conventional building materials:	DIN 18 542	Complies with requirements up to 600 Pa
Shelf life:		1 year (unopened original packaging)
Storage temperature:		+1 °C to +20 °C

*Important Notice*

*All GSAP products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning GSAP products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for GSAP products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.*