

Shireoak

25mm



Certified
Company



Chlorine
Resistant



Made in
Belgium



10 Year
Warranty



Eco
Friendly



Pet
Friendly



Child
Friendly



UV
Stability



Heavy
Usage

TECHNICAL SPECIFICATION

Fibre	65% PE, 35% PP
Fibre Shape	Xtra Spine Technology (XST)
Pile height	ca. 25 mm
Stitches	ca. 15 / 10 cm
Production	Tufting
Gauge	3/8"
Tufts	ca. 15.750 / m ²
Pile weight	ca. 642 gr / m ²
Total weight	ca. 1.512 gr / m ²
Tuft cloth	Polypropylene woven, ca. 170 gr / m ²
Backing	Pre coat, ca. 700 gr / m ²
Roll width	200 cm / 400 cm
Roll length	± 30 m
UV Stability	>3.000 hours UV-A 6,000 hours XENON
Light fastness	Scale 7 (DIN 54004)
Chlore resistance	4 – 5 (DIN 54019)
Resistance to sea water	4 – 5 (DIN 54007)

Address - Unit 1, West Way, Cotes Park Ind Est, Alfreton, Derby, DE55 4QJ

www.perma-lawn.co.uk



01773 608 808



info@perma-lawn.co.uk