
HR 612 C H

12NC: F104302

GTIN (EAN) code: 5054645043026







Product group	MAIN FEATURES		
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Plug type So/60 Length of Electrical Supply Cord (cm) Plug type Gas connection Width of the product Height of the product Depth of the product Minimum niche height Minch edepth Net weight (kg) Net weight (kg) Relectronic O Number of electrical connection Plug type No Gas connection So/60 Niche depth No	Product group	Hob	
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Plug type No Gas connection Plug type No Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minch depth Net weight (kg) Net weight (kg) Net weight (kg) Re O O O O O O O O O O O O O	Construction type	Built-in	
Number of gas burners 0 Number of electric cooking zones 4 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Type of control	Electronic	
Number of electric cooking zones 4 Number of electric plates 0 Number of radiant plates 4 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Type of control settings	-	
Number of electric plates 0 Number of radiant plates 4 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of gas burners	0	
Number of radiant plates 4 Number of induction plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 4700 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of electric cooking zones	4	
Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of electric plates	0	
Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 4700 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of radiant plates	4	
Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Plug type Cas connection Plug type Sas connection N/A Width of the product Depth of the product Minimum niche height Mich edepth Net weight (kg) Pront Front Front Ceramic Glass Black Electrical connection N/A 0 20 Voltage (W) 220-240/380-415 50/60 220-240/380-415 Frequency (Hz) 50/60 No 0 N/A Width of Electrical Supply Cord (cm) N/A Width of the product 580 Height of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth Net weight (kg)	Number of halogen plates	0	
Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Ength of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Niche depth Niche depth Net weight (kg) Front Ceramic Glass Radic Ceramic Glass RA700 0 20 V/A 220-240/380-415 50/60 220-240/380-415 50/60 10 No Gas connection N/A Width of the product F80 46 Depth of the product F10 Minimum niche width F60 Niche depth Net weight (kg) 8	Number of induction plates	0	
Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 4700 Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Number of electric warming zones	0	
Main colour of productBlackElectrical connection rating (W)4700Gas connection rating (W)0Gas typeN/ACurrent (A)20Voltage (V)220-240/380-415Frequency (Hz)50/60Length of Electrical Supply Cord (cm)0Plug typeNoGas connectionN/AWidth of the product580Height of the product46Depth of the product510Minimum niche height42Minimum niche width560Niche depth490Net weight (kg)8	Location of control panel	Front	
Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Elength of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Net weight (kg) 8	Basic surface material	Ceramic Glass	
Gas connection rating (W) 0 Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Main colour of product	Black	
Gas type N/A Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Electrical connection rating (W)	4700	
Current (A) 20 Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas connection rating (W)	0	
Voltage (V) 220-240/380-415 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas type	N/A	
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 0 Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Current (A)	20	
Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) O No No No No No No No No No	Voltage (V)	220-240/380-415	
Plug type No Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Frequency (Hz)	50/60	
Gas connection N/A Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Length of Electrical Supply Cord (cm)	0	
Width of the product 580 Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Plug type	No	
Height of the product 46 Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Gas connection	N/A	
Depth of the product 510 Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Width of the product	580	
Minimum niche height 42 Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Height of the product	46	
Minimum niche width 560 Niche depth 490 Net weight (kg) 8	Depth of the product	510	
Niche depth 490 Net weight (kg) 8	Minimum niche height	42	
Net weight (kg) 8	Minimum niche width	560	
- , -,	Niche depth	490	
Automatic programmes No	Net weight (kg)	8	
The second secon	Automatic programmes	No	

TECHNICAL FEAT	TURES
Power on indicator	Yes
Number of indicators	4
Type of regulation	Radiant
Type of lid	Without
Residual heat indicator	Separate
Main on/off switch	Yes
Safety device	-
Timer	Yes

PERFORMANCES	
Energy input	Electric