

PROFLOOR DYNAMIC DECK 26

PROFLOOR DYNAMIC DECK 26

Product specification to be Profloor Dynamic Deck 26 by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Acoustic Floating Floor System to be used shall be Profloor Dynamic Deck 26 supplied by The A Proctor Group, Blairgowrie. Profloor Dynamic Deck 26 is a T&G chipboard and open cell foam laminate with closed cell foam edge support strip. It is used to provide impact sound reduction in separating floors for both Refurbishment and New Build projects.

Product

Product performance specification as follows:

Standard Deck

26mm x 600mm x 2400mm

Hi-Load Deck

26mm x 600mm x 2400mm

Material

Open cell foam with closed cell support bonded to 18mm P5 grade T&G chipboard

Accessories

Flanking / Support Strip: 7mm x 125mm x 10m (available with or without double sided tape)

Profloor Adhesive: 1 litre bottles

Certification

Minimum required: The timber in should be responsibly sourced, being either FSC or PEFC certified.

Technical Properties

- Resilient Layer Composition: to be 8mm open cell foam and have patented edge strip to prevent joint fracture
- Chipboard: to be 18mm P5 grade
- Compression under normal loadings: Standard Deck to be no more than 1-2mm, Hi Load Deck to be no more than 1-2mm
- RD Compliance: FFT5
- Refurb Compliance: suitable for improving the impact sound reduction between existing separating floors
- Timber or Concrete Floor: to be suitable for use in timber and concrete floors

Profloor Dynamic Deck 26 provides the high degree of isolation necessary to give significant improvements in impact sound insulation. Profloor Dynamic Deck System utilises a patented edge support strip which prevents fracture of the tongue and grooved joint. Standard: for normal domestic loadings (up to 1.4kN/m²) Hi-load: for floors with higher loadings (up to 4.0kN/m²)

Benefits

- Robust Detail-compliant FFT5
- Standard thickness 26mm
- Hi-Load Grade available
- Suitable for both timber and concrete floors
- Simple to install-no multi-layer build up
- Dynamic Deck utilises 18mm P5 T&G moisture-resistant chipboard
- Patented edge support strip prevents joint fracture
- Foams are biologically stable
- Suitable for new build and refurbishment
- FSC certified

Product Reference [Profloor Dynamic Deck 26](#)

Revision Date: 28.05.2018