

ESSENTIAL SLIP-STOP

2.5L **5L** SKU: SC4U_ERS_ANT250 / SC4U_ERS_ANT05

DESCRIPTION

Permanent Anti-slip Floor Treatment

SC4U ESSENTIAL SLIP-STOP is a permanent anti-slip treatment uses mild acid solutions to microscopically treat ceramics, porcelain and natural stone to greatly improve slip-resistance on wet floor areas.

ESSENTIAL SLIP-STOP can be used on ceramic, porcelain & natural stone floors & showers and improves slip resistance on wet floors, providing long-term slip-fall accident protection. It is not suitable for use on vinyl, linoleum, wood, metal or coated surfaces.

DIRECTIONS FOR USE

- NOTE: Following the instructions below, perform a small test application in an inconspicuous area on-site prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Make sure surface is free from dirt, grease and oil. Apply Slip-Stop onto the area to be treated, in small sections. This can be done with a mop, sponge or dry cloth. Agitate wet surface with a stiff brush, let stand for 3-10 minutes. **DO NOT LET SOLUTION DRY ON SURFACE.**
- Reapply if necessary. When each area is completed, thoroughly rinse clean with water and then move onto the next area to be treated. Maximum slip-resistance is attained within 3-10 minutes depending on varying hard mineral surface material.
- Action time: 3-10 mins: Ceramic / Porcelain tiles, shower trays & baths 5-10 mins: Natural Stone & Masonry. A test patch must be completed prior to use to determine action time (dwell period) required, as the above times are only a guidance.

Important Note: Always protect areas not to be treated, Slip-Stop can cause permanent damage if accidentally spilt or applied on to sensitive surfaces, i.e. metals, painted surfaces, woods, glazed surfaces etc.

When properly applied and maintained, treated floors will have a slip coefficient exceeding slip-fall safety standards. SC4U will not accept any responsibility for misuse of this product.

COVERAGE

Up to 15m² per litre.
DO NOT DILUTE. Must be used neat.

USAGE GUIDELINES

Dwell Time	Applications/Coats	Application Method	Dilution
3-10 mins	1-2 applications	Mop/Sponge/ Cloth	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

- H314: Causes severe skin burns and eye damage.
- P102: Keep out of reach of children.
- P264: Wash hands thoroughly after handling.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321: Specific treatment (see instructions on this label).
- P405: Store locked up.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

