

ESSENTIAL BLACK TARMAc SEALER

5L **25L** SKU: SC4U_ERS_TAR05 / SC4U_ERS_TAR25

DESCRIPTION

Professional pigment-based sealer recolours & renews black tarmac / asphalt

SC4U ESSENTIAL BLACK TARMAc SEALER is formulated with a blend of technical acrylic resins that restore the original colour, flexibility and weather resistance of the tarmac surface. No need for expensive asphalt replacement, ESSENTIAL BLACK TARMAc SEALER replaces lost resin from tarmac, covers unsightly cement & oil stains or marks and brings the surface back to life. Ready to apply straight from the bottle, the quick and easy solution to renewing your tarmac.

Essential Black Tarmac Sealer is a long-lasting, pigment based sealer for tarmac and asphalt. Its unique formula contains a blend of technical acrylic resins which restore the original colour, flexibility and weather resistance of the tarmac surface.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e. gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Before any application, ensure the surface is thoroughly cleaned and loose stones etc. are thoroughly swept off, make sure weather conditions are favourable before commencing. Repair any damage/holes and kill off any weeds for the best possible finish. For best results it may be necessary to clean the tarmac by power washing the surface - if algae or moss are present a pre-treatment with **Essential Driveway Cleaner** will be necessary 4-5 days prior to applying the sealer.
- Use a smaller brush or roller to carefully apply **Essential Black Tarmac Sealer** to the edges/borders and fine lines to achieve a tidy finish. For larger areas, apply generously and evenly using a good quality floor roller. **DO NOT DILUTE.** Leave to dry for 45-60 mins.
- Apply a second coat, repeating the process applying the sealer in the opposite direction for even colour distribution. Where possible, leave overnight before driving or parking cars on the surface. Tarmac will be suitable for light foot traffic after 1-2 hours.

Please Note: Do not apply **Essential Black Tarmac Sealer** if rain is forecast within at least 3 hours of application. Always try product in an inconspicuous area prior to use. Surfaces which are not to be sealed should be protected with masking material.

COVERAGE

Up to 5M²/per litre per coat.
Coverage will vary greatly depending on the age, condition, surface porosity and texture of the tarmac.

USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2-3 coats	Brush/Sprayer/ Roller	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

- H302: Harmful if swallowed.
- H319: Causes serious eye irritation.
- P102: Keep out of reach of children.
- P233: Keep container tightly closed.
- P262: Do not get in eyes, on skin, or on clothing.
- P264: Wash skin thoroughly after handling.
- P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

