TECHNICAL APPLICATION GUIDE



ESSENTIAL BRICK SEALER





5L 25L SKU: SC4U_ERS_BRI05 / SC4U_ERS_BRI25

DESCRIPTION

Professional outdoor sealer for brickwork, masonry and porous vertical stone surfaces

SC4U ESSENTIAL BRICK SEALER is formulated with technical synthetic resins that seals and protects brick surfaces. The sealer offers excellent water repellency and helps to reduce efflorescence, moss and algae growth, ESSENTIAL BRICK SEALER offers long lasting protection and once sealed, the brick requires very little maintenance. Ready to apply straight from the bottle, the quick and easy solution to sealing your brickwork. Essential Brick Sealer is a technical, synthetic resin emulsion that significantly reduces the capillary water absorption of treated surfaces, but doesn't clog the pores or capillaries. It significantly reduces the potential for organic soiling and moss and algae growth, whilst allowing the surface material the ability to "breathe" and transfer moisture vapour.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application onsite in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.
- Before application the surface must be completely clean and dry. Application methods include a low pressure sprayer, roller, natural fibre brush or sponge.
- Apply Essential Brick Sealer, to saturation, two coats "wet on wet" are needed to ensure complete coverage. **DO NOT DILUTE.** Surface dry after 45-60 minutes. If rain is forecast or starts, then stop treatment immediately and cover the freshly impregnated areas, the surface is required to stay completely dry for the first 6 hours after application.

Please Note: Essential Brick Sealer may delicately enhance the natural colour of the brick surface - always try product in an inconspicuous area prior to use. Surfaces which are not to be sealed should be protected with masking material.

MAINTENANCE

Clean sealed areas with a mild, ph neutral cleaner or a very low concentration of our outdoor cleaner range. Do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Up to $15M^2$ /per litre per coat.

Dependant on porosity of surface. Check the surface after application to ensure full effectiveness of repellent.

USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats	Brush/Mop/ Roller	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed. H315: Causes skin irritation. H319: Causes serious eye irritation.

P102: Keep out of reach of children. P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce

vomiting.
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.

P3054351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice.

P337+313: If eye irritation persists: Get medical advice

Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

