

# ESSENTIAL SEALER'S GOLD COLOUR BOOST

**1L** **2.5L** **5L** SKU: SC4U\_ERS\_SGC01 / SC4U\_ERS\_SGC250 / SC4U\_ERS\_SGC05

## DESCRIPTION

SC4U ESSENTIAL SEALER'S GOLD COLOUR BOOST is a professional, all-purpose colour enhancing sealer for all types of natural internal stone - the gold standard your stone deserves.

SC4U ESSENTIAL SEALER'S GOLD COLOUR BOOST is a highly effective multi-purpose indoor stone sealer. It has been developed to offer excellent sealing and oil & stain resistance to ALL types of indoor stone surfaces, including slate, limestone, granite, quartz, sandstone, travertine, marble and more. SEALER'S GOLD saves you time and money, one sealer does it all! Essential Sealer's Gold Colour Boost is a very effective colour enhancer suitable for most common internal porous textured stone and masonry surfaces. Not recommended for use on highly polished, ceramic/glazed or non-porous surfaces.

## DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Before application the surface must be completely clean and dry, apply an even coat with a low pressure sprayer, roller, natural fibre brush or sponge, any excess sealer must be completely removed from the surface after 20-30 minutes.
- Apply a second application approximately 45-60 minutes repeating the process. After application it is important that the stone surface is kept completely dry through the curing process, up to 72 hours. Any moisture or water left on the surface within this time may result in the sealer drying inconsistent showing hard to remove white patches.

**Please Note:** Areas not to be sealed must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding.

## COVERAGE

Up to 25M<sup>2</sup> per litre.  
Dependant on porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

## USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats	Brush/Sprayer/ Roller/Sponge	Undiluted

## PRECAUTIONS

### KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.

P102: Keep out of reach of children.  
P262: Do not get in eyes, on skin, or on clothing.  
P280: Wear protective gloves.  
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
P302+350: IF ON SKIN: Gently wash with plenty of soap and water.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.  
P332+313: If skin irritation occurs: Get medical advice.  
P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from [www.stonecare4u.co.uk](http://www.stonecare4u.co.uk).

## STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

