

ESSENTIAL SLATE SEALER MATT FINISH

5L **25L** SKU: SC4U_ERS_SLM05 / SC4U_ERS_SLM25

DESCRIPTION

Professional performance natural slate sealer

SC4U ESSENTIAL SLATE SEALER MATT is a high performance stone sealer formulated especially for external natural slate surfaces. Also suitable for other porous natural stone such as sandstone and limestone. ESSENTIAL SLATE SEALER MATT provides excellent water repellency and long lasting protection. Once sealed, the attractive matt finish helps to prevent efflorescence, moss and algae growth and creates a self-cleaning surface tension that reduces the need for regular maintenance. The unique formula of Essential Slate Sealer Matt significantly reduces the capillary water absorption of the treated surface, but doesn't clog the pores or capillaries. This significantly reduces the potential for organic soiling and moss and algae growth, whilst allowing the surface material the ability to "breathe" and transfer moisture vapour.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Before application the surface must be completely clean and dry. Application methods include a low pressure sprayer, roller, natural fibre brush or sponge.
- Apply **Essential Slate Sealer Matt**, to saturation, two coats "wet on wet" are needed to ensure complete coverage. **DO NOT DILUTE.** Surface dry after 45-60 minutes. If rain is forecast or starts, then stop treatment immediately and cover the freshly impregnated areas, the surface is required to stay completely dry for the first 6 hours after application.

Please Note: Essential Slate Sealer Matt may cause a change of appearance/colour on some stone types. Surfaces which are not to be sealed should be protected with masking material. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED, CERAMIC/GLAZED, DENSE OR NON-POROUS SURFACES.**

MAINTENANCE

Clean sealed areas with a mild, ph neutral cleaner or a very low concentration of our outdoor cleaner range. Do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Up to 15M²/per litre per coat.

USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats	Sponge/Brush/ Sprayer/Roller	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

- H302: Harmful if swallowed.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 P102: Keep out of reach of children.
 P262: Do not get in eyes, on skin, or on clothing.
 P280: Wear protective gloves.
 P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.
 P332+313: If skin irritation occurs: Get medical advice.
 P337+313: If eye irritation persists: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

