

ESSENTIAL SLATE SEALER SATIN FINISH

5L **25L** SKU: SC4U_ERS_SLS05 / SC4U_ERS_SLS25

DESCRIPTION

Professional performance natural slate sealer

SC4U ESSENTIAL SLATE SEALER SATIN is a high performance stone sealer formulated especially for external natural slate surfaces. Also suitable for other porous natural stone such as limestone and sandstone. ESSENTIAL SLATE SEALER SATIN provides a hard wearing, attractive satin finish, that can intensify natural colours and offers high quality stain protection. Can also be applied to internal surfaces. Essential Slate Sealer Satin is quick drying and easy to apply. It provides high quality protection that prevents water-based stains and general grime & dirt from penetrating into the surface, making it easier to clean and maintain.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.**
- Before application the surface must be completely clean and dry, make sure weather conditions are favourable before commencing.
- Apply **Essential Slate Sealer Satin** thinly and evenly with either a low pressure sprayer, micro-fibre mop, paint brush or soft cloth, taking care not to leave application marks or allowing the product to puddle on the surface. **DO NOT DILUTE.**
- Allow 45-60 minutes drying time before applying the second coat, repeating the same process apply the product in the opposite direction to help to achieve an even consistent finish. If necessary more coats can be applied to achieve the desired "gloss" finish.

Please Note: Essential Slate Sealer Satin is likely to change the colour/appearance of some stone types. Surfaces which are not to be sealed should be protected with masking material. **NOT RECOMMENDED FOR USE ON HIGHLY POLISHED STONE & CERAMIC GLAZED SURFACES.**

MAINTENANCE

Clean sealed areas with a mild, ph neutral cleaner or a very low concentration of our outdoor cleaner range. Do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

COVERAGE

Up to 15M²/per litre per coat.

USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2-4 coats	Cloth/Brush/Sprayer/Mop	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

- H302: Harmful if swallowed.
 H319: Causes serious eye irritation.
 P102: Keep out of reach of children.
 P233: Keep container tightly closed.
 P262: Do not get in eyes, on skin, or on clothing.
 P264: Wash skin thoroughly after handling.
 P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.

