

ESSENTIAL PORCELAIN SEALER

1L **5L** SKU: SC4U_ERS_POS01 / SC4U_ERS_POS5

DESCRIPTION

Professional Porcelain tile sealer for indoor & outdoor use

SC4U ESSENTIAL PORCELAIN SEALER is an technically advanced, nano coating sealer formulated for modern engineered porcelain tiles and paving. ESSENTIAL PORCELAIN SEALER is a simple one-coat, 100% breathable formula. Application will protect and inhibit organic growth, dirt and staining, whilst enhancing the natural colours with a subtle sheen. Ready to use formula, quick drying and easy to apply. **Not recommended for use on highly polished surfaces.**

Essential Porcelain Sealer is a professional sealer for use on modern outdoor and indoor porcelain tiling. The safe, water-based formula creates a durable, clear soft sheen, scratch resistant finish.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED.**
- Before application the surface must be completely clean and dry, make sure weather conditions are favourable before commencing externally.
- DO NOT DILUTE.** Apply **Essential Porcelain Sealer** thinly and evenly with either a microfibre cloth, microfibre flat mop or paint pad, taking care not to leave application marks or allowing the product to puddle on the surface.
- Allow a minimum of 2 hours drying time before walking on. The sealer will be fully-cured and attain full water-resistance after 24 hours. If using externally, do not apply if rain is forecast within 8 hours.

Please Note: This formulation is strictly a single coat application, because it is a high active micro coating that bonds very strongly to the impervious porcelain. Applying more than one coat to achieve the “desired appearance” will almost definitely result in application issues and product failure. Given the above, it is important the exact application instructions are followed.

COVERAGE

Average coverage of 10-20²/per litre.
Coverage will vary depending on surface texture and porosity.

MAINTENANCE

Clean sealed areas with a mild, ph neutral cleaner. Do not use harsh or abrasive cleaning agents as this can have a negative effect on the treated surface.

USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
2 hours	1 coat	Microfibre Cloth/ Microfibre Flat Mop/Paint Pad	Undiluted

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

- H302: Harmful if swallowed.
- H319: Causes serious eye irritation.
- P102: Keep out of reach of children.
- P233: Keep container tightly closed.
- P262: Do not get in eyes, on skin, or on clothing.
- P264: Wash skin thoroughly after handling.
- P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
- P302+350: IF ON SKIN: Gently wash with plenty of soap and water.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P333+313: If skin irritation or rash occurs: Get medical advice.



Product SDS sheet available to download from our website.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user’s responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 6 months of purchase. Once open, use within 3 months.

